

	OSAWA NORM
PAGE 253-254	

UHMB2 - UH253

Ø mm	-0.8	≥0.8
tol. D µ	0 / -12	0 / -20
tol. R µ	0 / -20	0 / -20

UHCSB2 - UH250

Ø mm	~6	>6
tol. D µ	0 / -12	0 / -15
tol. R µ	±5	±10



D	d	l	l1	L	Stock	Stock	Stock	Stock
mm 0.2	4	0.4		40	●			
0.2	6	0.2		40		■		
0.3	4	0.6		40	●			
0.4	4	0.8		40	●			
0.4	6	0.4		40		■		
0.5	4	1.2		40	●			
0.5	6	1.2		50		●		
0.6	4	1.4		40	●			
0.6	6	0.6		40		■		
0.6	6	1.4		50		●		
0.7	4	1.6		40	●			
0.8	4	1.8		40	●			
0.8	6	0.8		40		■		
0.8	6	1.8		50		●		
0.9	4	2		40	●			
0.9	6	0.9		40		■		
1	6	1.5		40		●		
1	4	1	2.2	50			●	
1	6	3	7	75				●
1	6	3	10	100				●
1.5	6	2.5		40		●		
1.5	4	1.5	3	50			●	
1.5	6	3	10	75				●
1.5	6	3	15	100				●
2	6	3		40		●		
2	6	2	4	50			●	
2	6	4	14	75				●
2	6	4	20	100				●
2.5	6	3		50		●		
2.5	6	4	18	75				●
2.5	6	4	25	100				○
3	6	4.5		50		●		
3	6	3	6	60			●	
3	6	5	21	75				●
3	6	5	30	100				●
4	6	6		50		●		

● stock standard ○ non-standard stock ■ stock exhaustion