

	OSAWA NORM
PAGE 253-254	

UHMB2 - UH253

Ø mm	-0.8	≥0.8
tol. D μ	0 / -12	0 / -20
tol. R μ	0 / -20	0 / -20

UHCSB2 - UH250

Ø mm	~6	>6
tol. D μ	0 / -12	0 / -15
tol. R μ	±5	±10



D	d	l	l1	L	Stock	Stock	Stock	Stock
mm	4	6	4	8	70			
	4	6	4	40	100			
	5	6	7.5	50				
	5	6	5	10	80			
	5	6	5	50	100			
	6	6	9	50				
	6	6	6	12	90			
	6	6	10	60	100			
	6	6	10	60	150			
	8	8	12	50				
	8	8	8	16	100			
	8	8	12	60	100			
	8	8	12	80	150			
	10	10	15	60				
	10	10	10	20	100			
	10	10	14	85	125			
	10	10	14	100	150			
	12	12	18	60				
	12	12	12	24	110			
	12	12	16	85	125			
	12	12	16	110	150			

● stock standard ○ non-standard stock ■ stock exhaustion

- TYPHOON
- C-SD-TA
- LFTA
- SUTA
- HSS-HSS/CO DRILLS
- UH RED
- MEX ORANGE
- HF EVO
- MEF ENDLESS
- ALU
- MDC
- G2
- MDTA
- ULTRA MILLS
- HSS/CO
- CARBIDE BURRS
- PARAMETERS