

**n** **Vf**  
PAGE 255~257

**OSAWA NORM**

**NEW**




**UHCRB2**

Ø mm	~6
tol. D µ	0 / -12
tol. R µ	±5

**UHLNB2**

Ø mm	~0.8	≥0.8
tol. D µ	0 / -12	0 / -20
tol. R µ	0 / -20	0 / -20



$d_1 < D$


D	d	l	l1	L	Stock	Stock
mm 0.1	4	0.1	0.3	45	■	●
0.2	4	0.2	0.5	50	■	●
0.2	4	0.2	1	45	■	●
0.2	4	0.2	1.5	50	■	●
0.3	4	0.3	1	50	■	●
0.3	4	0.3	2	45	■	●
0.3	4	0.3	2	50	■	●
0.3	4	0.3	3	50	■	●
0.4	4	0.4	1	45	■	●
0.4	4	0.4	1	50	■	●
0.4	4	0.4	2	50	■	●
0.4	4	0.4	3	50	■	●
0.4	4	0.4	4	50	■	●
0.5	6	0.5	2	45	●	●
0.5	4	0.4	2	50	●	●
0.5	4	0.4	3	50	●	●
0.5	6	0.5	4	45	●	●
0.5	4	0.4	4	50	●	●
0.5	4	0.4	5	50	●	●
0.5	4	0.4	6	45	■	●
0.5	4	0.4	6	50	■	●
0.5	4	0.4	8	50	■	●
0.6	4	0.5	2	50	●	●
0.6	4	0.5	3	50	●	●
0.6	6	0.6	4	45	●	●
0.6	4	0.5	4	50	●	●
0.6	4	0.5	5	50	●	●
0.6	4	0.6	6	45	■	●
0.6	4	0.5	6	50	●	●
0.6	4	0.5	8	50	●	●
0.8	4	0.6	2	50	●	●
0.8	6	0.8	2	45	●	●
0.8	4	0.6	4	50	●	●
0.8	4	0.6	6	50	●	●
0.8	6	0.8	6	45	●	●

● stock standard ○ non-standard stock ■ stock exhaustion