

PAGE 264-265

OSAWA
NORM

UH411 - UH412

Ø mm	~6	>6
tol. D µ	0 / -12	0 / -15
tol. R µ	±10	±15



Z4

NMG
UH RED

UH RADIUS

30°

Z4

NMG
UH RED

UH RADIUS

30°

D	d	l	l1	L	Stock	Stock	
mm 2	R0.3	6	4	30	75		
2	R0.3	6	4	60	100		● NEW
3	R0.3	6	4	12	55	●	
3	R0.3	6	4	20	60	●	
3	R0.3	6	5	30	75		● NEW
3	R0.3	6	5	60	100		● NEW
3	R0.5	6	4	10	55	●	
3	R0.5	6	4	20	60	●	
3	R0.5	6	5	30	75		● NEW
3	R0.5	6	5	60	100		● NEW
4	R0.3	6	6	12	55	●	
4	R0.3	6	6	20	60	●	
4	R0.3	6	8	32	75		● NEW
4	R0.3	6	8	60	100		● NEW
4	R0.5	6	6	12	55	●	
4	R0.5	6	6	20	60	●	
4	R0.5	6	8	32	75		● NEW
4	R0.5	6	8	60	100		● NEW
4	R1.0	6	6	12	55	●	
6	R0.5	6	9	15	60	●	
6	R0.5	6	9	20	90		●
6	R1.0	6	9	15	60	●	
6	R1.0	6	9	20	90		●
8	R0.5	8	12	20	70	●	
8	R0.5	8	12	25	100		●
8	R1.0	8	12	20	70	●	
8	R1.0	8	12	25	100		●
8	R2.0	8	12	20	70	●	
10	R0.5	10	15	25	70	●	
10	R0.5	10	15	32	100		●
10	R1.0	10	15	25	70	●	
10	R1.0	10	15	32	100		●
10	R2.0	10	15	25	70	●	
10	R2.0	10	15	32	100		●
12	R0.5	12	18	30	80	●	
12	R0.5	12	18	38	110		●
12	R1.0	12	18	30	80	●	
12	R1.0	12	18	38	110		●
12	R2.0	12	18	30	80	●	
12	R2.0	12	18	38	110		●

● stock standard ○ non-standard stock ■ stock exhaustion