

OSAWA NORM

MEXMB2 - MEX253		
Ø mm	~0.8	≥0.8
tol. D μ	0 / -12	0 / -20
tol. R μ	0 / -20	0 / -20
MEXCLSB2		
Ø mm	~6	>6
tol. D μ	0 / -12	0 / -15
tol. R μ	±10	±10
MEXCSB2		
tol. D μ	0 / -30	0 / -30
tol. R μ	±10	±10



MEXMB2				
MEXCSB2 MEXCLSB2 MEX253				

D	d	l	l1	L	Stock	Stock	Stock	Stock
mm 0.2	4	0.4		40	●			
0.3	4	0.6		40	●			
0.4	4	0.8		40	●			
0.5	4	1.2		40	●			
0.6	4	1.4		40	●			
0.7	4	1.6		40	●			
0.8	4	1.8		40	●			
0.9	4	2		40	●			
1	3	3		38		●		
1	4	3		40	●			
1	4	2.5		50			●	
1 NEW	4	3		75				●
1 NEW	4	3		100				●
1.2	4	3		50			●	
1.5	3	3		38		●		
1.5	4	3		40	●			
1.5	4	4		50			●	
1.5 NEW	4	3		75				●
1.5 NEW	4	3		100				●
2	4	4		40	●			
2	6	3		50		●		
2	6	5		50			●	
2 NEW	4	4		75				●
2 NEW	6	4		80				■
2 NEW	4	4		100				●
2.5	4	4		40		●		
2.5	6	6		60			●	
3	6	4		50		●		
3	6	8		60			●	
3 NEW	6	5		75				●
3	6	5		100				●
4	6	5		54		●		
4	6	8		70			●	
4	6	8		100				●
5	6	6		54		●		
5	6	10		80			●	
5 NEW	6	9		100				●

● stock standard ○ non-standard stock ■ stock exhaustion