

**n** **Vf**  
PAGE 267

**OSAWA**  
**NORM**

<b>MEXMB2 - MEX253</b>		
Ø mm	~0.8	≥0.8
tol. D µ	0 / -12	0 / -20
tol. R µ	0 / -20	0 / -20
<b>MEXCLSB2</b>		
Ø mm	~6	>6
tol. D µ	0 / -12	0 / -15
tol. R µ	±10	±10
<b>MEXCSB2</b>		
tol. D µ	0 / -30	0 / -30
tol. R µ	±10	±10

**MEXMB2 MEXCSB2 MEXCLSB2 MEX253**



<p>MEXMB2</p>	<p>Z2 BALL</p> <p>UMG ENDLESS ORANGE</p> <p>MEX BALL NOSE</p> <p>30°</p>	<p>Z2 BALL</p> <p>UMG ENDLESS ORANGE</p> <p>MEX BALL NOSE</p> <p>30°</p>	<p>Z2 BALL</p> <p>UMG ENDLESS ORANGE</p> <p>MEX BALL NOSE</p> <p>30°</p>	<p>Z2 BALL</p> <p>UMG ENDLESS ORANGE</p> <p>MEX BALL NOSE</p> <p>30°</p>

D	d	l	l1	L	Stock	Stock	Stock	Stcok
mm 5	6	10		120				○
6	6	12		60		●		
6	6	12		90			●	
6	6	12		120				○
6	<b>NEW</b> 6	10		150				●
7	8	8		58			○	
8	8	14		60		●		
8	8	14		100			●	
8	8	12		150				●
10	10	18		70				
10	10	18		100		●		
10	<b>NEW</b> 10	14		150				●
10	10	20		180				○
12	12	22		80		●		
12	12	22		110			●	
12	<b>NEW</b> 12	16		150				●
12	12	24		200				○
14	14	32		90		●		
14	14	32		125			●	
16	16	32		90		●		
16	16	32		150			●	
16	<b>NEW</b> 16	32		200				○
18	18	38		100		○		
20	20	38		100		○		
20	20	38		150			○	
20	<b>NEW</b> 20	38		200				○
22	22	40		100		○		
25	25	40		100		○		

● stock standard ○ non-standard stock ■ stock exhaustion

- TYPHOON
- C-SD-TA
- LFTA
- SUTA
- HSS-HSS/CO DRILLS
- UH RED
- MEX ORANGE
- HF EVO
- MEF ENDLESS
- ALU
- MDC
- G2
- MDTA
- ULTRA MILLS
- HSS/CO
- CARBIDE BURRS
- PARAMETERS