

n **Vf**
PAGE 268~270

OSAWA NORM

NEW

MEXCRB2 MEXLNB2

MEXCRB2

Ø mm	-6
tol. D µ	0 / -12
tol. R µ	±10

MEXLNB2

Ø mm	-0.8	≥0.8
tol. D µ	0 / -12	0 / -20
tol. R µ	0 / -20	0 / -20



$d_1 < D$

Z2 BALL

UMG
ENDLESS ORANGE

MEX BALL NOSE

30°

Z2 BALL

UMG
ENDLESS ORANGE

MEX BALL NOSE

30°

D	d	l	l1	L	Stock	
0.8	4	0.6	8	50		●
0.8	6	0.8	8	60		●
0.8	4	0.6	10	50		●
1	4	0.8	3	50		●
1	4	0.8	4	50		●
1	4	0.8	5	50		●
1	6	1.5	5	60		●
1	4	1	6	45	●	
1	4	0.8	6	50		●
1	4	1	8	45	●	
1	4	0.8	8	50		●
1	6	1.5	8	60		●
1	4	0.8	10	50		●
1	4	1	12	45	●	
1	4	0.8	12	50		●
1	6	1.5	12	60		●
1	4	0.8	14	50		●
1	4	1	16	50	●	
1	4	0.8	16	50		●
1	4	1	20	55	■	
1	4	0.8	20	60		●
1.2	4	1	6	50		●
1.2	6	1.8	6	60		●
1.2	4	1.2	8	45	■	
1.2	4	1	8	50		●
1.2	4	1	10	50		●
1.2	4	1.2	12	45	■	
1.2	4	1	12	50		●
1.4	4	1.1	8	50		●
1.4	4	1.4	12	45	■	
1.4	4	1.1	12	50		●
1.4	4	1.1	16	50		●
1.5	4	1.5	8	45	●	
1.5	4	1.2	8	50		●
1.5	6	2.3	8	60		●
1.5	4	1.5	12	45	●	

● stock standard ○ non-standard stock ■ stock exhaustion

- TYPHOON
- C-SD-TA
- LFTA
- SUTA
- HSS-HSS/CO DRILLS
- UH RED
- MEX ORANGE**
- HF EVO
- MEF ENDLESS
- ALU
- MDC
- G2
- MDTA
- ULTRA MILLS
- HSS/CO
- CARBIDE BURRS
- PARAMETERS