

n **Vf**
PAGE 268~270

OSAWA NORM

NEW

MEXCRB2 MEXLNB2

MEXCRB2

Ø mm	-6
tol. D µ	0 / -12
tol. R µ	±10

MEXLNB2

Ø mm	-0.8	≥0.8
tol. D µ	0 / -12	0 / -20
tol. R µ	0 / -20	0 / -20



$d_1 < D$

Z2 BALL

UMG
ENDLESS ORANGE

MEX BALL NOSE

30°

Z2 BALL

UMG
ENDLESS ORANGE

MEX BALL NOSE

30°

D	d	l	l1	L	Stock	
mm 2	4	1.6	22	60		○
2	4	1.6	25	75		●
2	4	2	26	70	■	
2	4	2	30	70	■	
2	4	1.6	30	75		●
3	6	2.4	8	50		●
3	6	2.4	10	50		●
3	6	3	16	55	●	
3	6	2.4	16	60		●
3	6	3	20	60	●	
3	6	2.4	20	60		●
3	6	2.4	25	75		●
3	6	3	26	70	■	
3	6	3	30	70	●	
3	6	2.4	30	75		●
3	6	2.4	35	75		●
4	6	3.2	10	50		●
4	6	4	16	60	●	
4	6	3.2	16	60		●
4	6	3.2	20	60		●
4	6	4	20	65	●	
4	6	3.2	25	75		●
4	6	4	26	70	■	
4	6	4	30	70	■	
4	6	3.2	30	75		●
4	6	3.2	35	75		●
4	6	4	40	90	■	
4	6	3.2	40	100		●
4	6	3.2	50	100		●
5	6	5	20	60	■	
5	6	5	30	80	■	
6	6	6	30	90	■	
6	6	6	40	100	■	
6	6	6	50	110	■	

● stock standard ○ non-standard stock ■ stock exhaustion

- TYPHOON
- C-SD-TA
- LFTA
- SUTA
- HSS-HSS/CO DRILLS
- UH RED
- MEX ORANGE**
- HF EVO
- MEF ENDLESS
- ALU
- MDC
- G2
- MDTA
- ULTRA MILLS
- HSS/CO
- CARBIDE BURRS
- PARAMETERS