

n Vf  
 PAGE 271-272

**OSAWA NORM**

<b>MEXM2</b>		
Ø mm	~0.8	≥0.8
tol. D µ	0 / -12	0 / -20
<b>MEXCS2</b>		
Ø mm	~25	
tol. D µ	0 / -12	
<b>MEXCL2</b>		
Ø mm	~16	
tol. D µ	0 / -30	



<p>MEXM2</p>	<p>MEXCS2 MEXCL2</p>	   	   	   
--------------	--------------------------	--------------	--------------	--------------

D	d	l	l1	L	Stock	Stock	Stock
mm 0.1	4	0.2		40	●		
0.2	4	0.4		40	●		
0.3	4	0.6		40	●		
0.4	4	0.8		40	●		
0.5	4	1		40	●		
0.6	4	1.2		40	●		
0.7	4	1.4		40	●		
0.8	4	1.6		40	●		
0.9	4	1.8		40	●		
1	3	2		40	●		
1	4	2.5		40		●	
1	6	8		60			●
1.1	3	2.2		40	●		
1.1	4	2.5		40	●		
1.2	3	2.4		40	●		
1.2	4	4		40	●		
1.3	3	2.6		40	●		
1.4	3	2.8		40	●		
1.4	4	4		40	●		
1.5 <b>NEW</b>	3	3		40	●		
1.5	4	4		40		●	
1.5	6	12		60			●
1.6 <b>NEW</b>	3	3.2		40	●		
1.7 <b>NEW</b>	3	3.4		40	●		
1.8 <b>NEW</b>	3	3.6		40	●		
1.9 <b>NEW</b>	3	3.8		40	●		
2 <b>NEW</b>	3	4		40	●		
2	4	6		40		●	
2	6	12		60			●
2.5	4	8		40		●	
3	6	8		55		●	
3	6	15		60			●
3.5	6	10		55		●	
4	6	10		55		●	
4	6	20		60			●
4.5	6	12		55		●	

● stock standard   ○ non-standard stock   ■ stock exhaustion