

n **Vf**
PAGE 284-285

OSAWA NORM

Ø mm	3-20
tol. D µ	0 / -30
tol. R µ	±10



UNEQUAL PITCH

VARIABLE HELIX

MG	MG	MG	MG	MG
PV300	PV300	PV300	PV300	PV300

D	R	d(h6)	l	l1	L	Stock	Stock	Stock	Stock	Stock	
mm 12	3	12	26		83	●				●	
	14	1	14	26		83	●				
		1	14	26	36	83		●	●		
		1	14	32		83				●	
16	2	14	26		83	○					
	2	14	32		83				○		
	3	14	26		83	○					
	18	1	16	32		92	●			●	
		1	16	32	42	92		●	●		●
		2	16	32		92	●			●	
		2	16	32	42	92		●			●
20	3	16	32		92	●			○		
	4	16	32		92	○			○		
	18	2	18	32		92	○				
		3	18	32		92	○				
20	1	20	38		104	●			●		
	1	20	38	50	104		●	●		●	
	2	20	38		104	●			●		
	2	20	38	50	104		●			●	
	3	20	38		104	○			○		
	4	20	38		104	○			○		

● stock standard ○ non-standard stock ■ stock exhaustion

- TYPHOON
- C-SD-TA
- LFTA
- SUTA
- HSS-HSS/CO DRILLS
- UH RED
- MEX ORANGE
- HF EVO
- MEF ENDLESS
- ALU
- MDC
- G2
- MDTA
- ULTRA MILLS
- HSS/CO
- CARBIDE BURRS
- PARAMETERS