

PAGE 284-285

OSAWA
NORM

| | |
|----------|---------|
| Ø mm | 6-20 |
| tol. D µ | 0 / -50 |
| tol. R µ | ±20 |



| | | | | | | Z4 | Z4 | Z4 | |
|-------------|---------|-------|----|----|-----|--------|--------|--------|--|
| D | C (45°) | d(h6) | l | l1 | L | Stock | Stock | Stock | |
| mm 6 | 0,1 | 6 | 13 | 20 | 57 | ● | ● | ● | |
| | 0,1 | 6 | 16 | | 57 | ● | | | |
| 8 | 0,2 | 8 | 20 | | 64 | ● | | | |
| | 0,2 | 8 | 20 | 26 | 64 | ● | ● | ● | |
| 10 | 0,2 | 10 | 22 | | 72 | ● | | | |
| | 0,2 | 10 | 22 | 30 | 72 | ● | ● | ● | |
| 12 | 0,2 | 12 | 26 | | 83 | ● | | | |
| | 0,2 | 12 | 26 | 36 | 83 | ● | ● | ● | |
| 14 | 0,3 | 14 | 26 | | 83 | ● | | | |
| | 0,3 | 14 | 26 | 36 | 83 | ● | ● | ● | |
| 16 | 0,3 | 16 | 32 | | 92 | ● | | | |
| | 0,3 | 16 | 32 | 42 | 92 | ● | ● | ● | |
| 18 | 0,3 | 18 | 32 | | 92 | ● | | | |
| 20 | 0,4 | 20 | 38 | | 104 | ● | | | |
| | 0,4 | 20 | 38 | 50 | 104 | ● | ● | ● | |

● stock standard ○ non-standard stock ■ stock exhaustion