

n **Vf**
PAGE 292

**OSAWA
NORM**

Ø mm	<0.8	>0.8
tol. D µ	0 / -12	0 / -20
tol. R µ	0 / -20	0 / -20



MDC	MDC	MDC

D	d	l	l1	L	Stock	Stock	Stock
mm 0.5	4	1	6	50		●	
0.6	4	1.2	6	50		●	
0.8	4	1.6	8	50		●	
1	3	3		40	●		
1	4	3	10	60		●	
1.5	3	3		40	●		
1.5	4	3	15	60		●	
2	3	4		40	●		
2	4	4	20	60		●	
2	4	10	20	80			■
2.5	3	4		40	●		
2.5	4	4	25	60		●	
3	3	5		40	●		
3	4	15	25	80			■
3	4	15	25	100			●
3	3	5	30	100		●	
4	4	8		50	●		
4	4	20	30	80			■
4	4	20	30	100			●
4	4	8	40	100		●	
5	5	9		50	●		
5	5	9	50	100		●	
5	6	30	50	100			■
5	6	30	50	120			●
6	6	10		60	●		
6	6	10	60	100		●	
6	6	30	50	100			■
6	6	30	50	150			●
8	8	12	60	100		●	
8	8	40	60	150			●
10	10	14	60	100		●	
12	12	16	60	100		●	

● stock standard ○ non-standard stock ■ stock exhaustion