

n **Vf**
PAGE 292-293

OSAWA NORM

Ø mm	<0.8	>0.8
tol. D µ	0 / -12	0 / -20



Z2

MG

MDC

40°

Z4

MG

MDC

40°

D	d	l	l1	L	Stock	Stock
mm 0.5	4	1	6	50	●	●
0.6	4	1.2	6	50	●	●
0.8	4	1.6	8	50	●	●
1	4	3	10	60	●	●
1.5	4	4.5	15	60	●	●
2	4	6.5	20	60	●	●
2.5	4	6.5	25	60	●	●
3	3	9	30	75	●	●
3	3	19	30	100	●	●
4	4	12	32	75	●	●
4	4	25	40	100	●	●
5	5	15	32	75	●	●
5	5	25	60	100	●	●
6	6	25	60	100	●	●
8	8	25	60	100	●	●
10	10	25	60	100	●	●
12	12	25	60	100	●	●

● stock standard ○ non-standard stock ■ stock exhaustion

TYPHOON

C-SD-TA

LFTA

SUTA

HSS-HSS/CO DRILLS

UH RED

MEX ORANGE

HF EVO

MEF ENDLESS

ALU

MDC

G2

MDTA

ULTRA MILLS

HSS/CO

CARBIDE BURRS

PARAMETERS