


	OSAWA NORM
PAGE 294	

GB305 - G2CSH3

Ø mm	~6	6.5~12	13~20
tol. D µ	0 / -20	0 / -25	0 / -30

G2310 - G2311 - G2312

Ø mm	~6	6.5~12	13~20
tol. D µ	0 / -30	0 / -35	0 / -40



MG	MG	MG	MG	MG
BR	PV200	PV200	PV200	PV200
N	N	N	N	N

D	d	l	L	Stock	Stock	Stock	Stock	Stock
mm 1	4	3	50	●	●			
1.5	4	4.5	50	●	●			
2	4	6	50	●	●			
2	4	9	75			●		
2.5	4	7	50		●			
3	4	8	50	●	●			
3	4	15	75			●		
3.5	4	10	50		●			
4	4	11	50	●	●			
4	4	20	75			●		
4.5	6	13	50		●			
5	6	13	50	●	●			
5	6	25	75			●		
5	6	30	100				●	
5.5	6	13	50		●			
6	6	15	50	●	●			
6	6	25	75			●		
6	6	30	100				●	
6.5	8	17	60		●			
7	8	17	60		●			
7	8	35	100				○	
7.5	8	17	60		●			
8	8	20	60	●	●			
8	8	35	100				●	
8	8	40	150					●
8.5	10	23	75		●			
9	10	23	75		●			
9	10	40	100				○	
10	10	30	75	●	●			
10	10	40	100				●	
10	10	50	150					●
10.5	12	25	75		○			
11	12	28	75		●			
11	12	45	100				○	
12	12	30	75	●	●			
12	12	45	100				●	

● stock standard ○ non-standard stock ■ stock exhaustion