

	OSAWA NORM
PAGE 295-296	

G2CSFR - G2WSFR

Ø mm	~20
tol. D µ	0 / -50



<p>G2CSFR</p>	<p>G2WSFR</p>	<p>Z3-Z4</p>	<p>Z3-Z4</p>
		<p>MG PV200</p>	<p>MG PV200</p>
		<p>HR FINE</p>	<p>HR FINE</p>
		<p>30°</p>	<p>30°</p>

D	d	l	L	Z	Stock	Stock
mm 6	6	15	50	3	●	
8	8	20	60	3	●	
10	10	30	75	4	●	
12	12	30	75	4	●	
14	14	30	83	4	●	
16	16	35	92	4	●	
20	20	40	100	4	●	
6	6	13	57	3		●
8	8	19	63	3		●
10	10	22	72	4		●
12	12	26	83	4		●
14	14	26	83	4		●
16	16	32	92	4		●
20	20	38	104	4		●

● stock standard ○ non-standard stock ■ stock exhaustion

- TYPHOON
- C-SD-TA
- LFTA
- SUTA
- HSS-HSS/CO DRILLS
- UH RED
- MEX ORANGE
- HF EVO
- MEF ENDLESS
- ALU
- MDC
- G2**
- MDTA
- ULTRA MILLS
- HSS/CO
- CARBIDE BURRS
- PARAMETERS