

PAGE 294-295

OSAWA
NORM

Ø mm	~6	8-12
tol. D µ	0 / -20	0 / -25
tol. R µ	± 10	± 10



G2CS2R

G2CS4R

Z2

Z4

MG

PV200

MG

PV200

G2 RADIUS

G2 RADIUS

30°

30°

D	d	l	L	Stock	Stock
mm 1 R0.2	4	2	50	●	●
1.5 R0.2	4	3	50	●	●
1.5 R0.5	4	3	50	●	●
2 R0.2	4	4	50	●	●
2 R0.5	4	4	50	●	●
2.5 R0.2	4	5	50	●	●
2.5 R0.5	4	5	50	●	●
3 R0.2	4	6	50	●	●
3 R0.5	4	6	50	●	●
3 R1	4	6	50	●	●
4 R0.2	4	8	50	●	●
4 R0.5	4	8	50	●	●
4 R1	4	8	50	●	●
5 R0.5	6	10	50	●	●
5 R1	6	10	50	●	●
6 R0.2	6	12	50	●	●
6 R0.5	6	12	50	●	●
6 R1	6	12	50	●	●
6 R1.5	6	12	50	●	●
6 R2	6	12	50	●	●
8 R0.5	8	16	60	●	●
8 R1	8	16	60	●	●
8 R1.5	8	16	60	●	●
8 R2	8	16	60	●	●
10 R0.5	10	20	75	●	●
10 R1	10	20	75	●	●
10 R1.5	10	20	75	●	●
10 R2	10	20	75	●	●
10 R2.5	10	20	75	○	●
10 R3	10	20	75	○	●
12 R0.5	12	24	75	●	●
12 R1	12	24	75	●	●
12 R1.5	12	24	75	●	●
12 R2	12	24	75	●	●
12 R2.5	12	24	75	○	●
12 R3	12	24	75	○	●

● stock standard ○ non-standard stock ■ stock exhaustion

- TYPHOON
- C-SD-TA
- LFTA
- SUTA
- HSS-HSS/CO DRILLS
- UH RED
- MEX ORANGE
- HF EVO
- MEF ENDLESS
- ALU
- MDC
- G2**
- MDTA
- ULTRA MILLS
- HSS/CO
- CARBIDE BURRS
- PARAMETERS