

	OSAWA NORM
PAGE 296-297	

GB255 - G2CSB2 - G2CSB4

Ø mm	~6	7~12	14~20
tol. D µ	0 / -20	0 / -25	0 / -30
tol. R µ	±15	±15	0 / -30

G2250 - G2251

Ø mm	~6	7~12	14~20
tol. D µ	0 / -25	0 / -30	0 / -35
tol. R µ	±15	±15	0 / -30



	MG	MG	MG	MG	MG
	BR	PV200	PV200	PV200	PV200

D	d	l	L	Stock	Stock	Stock	Stock	Stock
mm 1	4	2	50	●	●	●	●	○
1	4	2	75	●	●	●	●	○
1.5	4	3	50	●	●	●	●	○
1.5	4	3	75	●	●	●	●	○
2	4	4	50	●	●	●	●	●
2	4	4	75	●	●	●	●	●
2.5	4	5	50	●	●	●	●	○
3	4	6	50	●	●	●	●	●
3	4	6	75	●	●	●	●	●
4	4	8	50	●	●	●	●	●
4	4	8	75	●	●	●	●	●
5	6	10	50	●	●	●	●	●
5	6	10	75	●	●	●	●	●
6	6	12	50	●	●	●	●	●
6	6	12	100	●	●	●	●	●
6	6	12	150	●	●	●	○	○
7	8	14	60	●	○	●	○	○
8	8	16	60	●	●	●	●	●
8	8	16	100	●	●	●	●	●
8	8	16	150	●	○	●	○	○
9	10	18	75	●	○	●	○	○
10	10	20	75	●	●	●	●	●
10	10	20	100	●	●	●	●	●
10	10	20	150	●	●	●	○	○
12	12	24	75	●	●	●	○	●
12	12	24	100	●	●	●	○	●
12	12	24	150	●	●	●	○	○
16	16	30	92	●	●	●	○	○
16	16	30	150	●	●	●	○	○
20	20	30	100	●	●	●	○	○
20	20	30	150	●	●	●	○	○

● stock standard ○ non-standard stock ■ stock exhaustion