

n Vf
 PAGE 294

**OSAWA
NORM**


MDTACS2 - MDTA210

Ø mm	1~20
tol. D µ	0 / -30

MDCL2 - MDACL2 (h10)

Ø mm	1~3	3.5~6	7~10	12~18	20~30
tol. D µ	0 / -40	0 / -48	0 / -58	0 / -70	0 / -84

MDTACS2 MDTA210 MDCL2



MG	MG	MG		
PV200	PV200	BR		
N	N	N		

D	d(h6)	l	L	Stock	Stock	Stock
mm 1	4	3	40	●		
1.5	4	4.5	40	●		
2	2	8	32	●		
2.5	2.5	8	32	●		
3	3	12	32	●		
3	3	20	60		●	
3	3	30	75			●
4	4	12	40	●		
4	4	20	60		●	
4	4	30	75			●
5	5	14	50	●		
5	5	25	75		●	
5	5	40	100			●
6	6	16	50	●		
6	6	30	75		●	
6	6	50	150			●
7	7	20	60	●		
8	8	20	60	●		
8	8	30	75		●	
8	8	50	150			●
9	9	20	60	●		
10	10	22	70	●		
10	10	40	100		●	
10	10	60	150			●
12	12	22	70	●		
12	12	45	100		●	
12	12	75	150			●
14	14	25	75	●		
14	14	45	100		●	
14	14	65	150			○
16	16	25	75	●		
16	16	45	100		●	
16	16	65	150			○
20	20	32	100	●		
20	20	65	150			○

● stock standard ○ non-standard stock ■ stock exhaustion