

n **Vf**
PAGE 294

**OSAWA
NORM**

MDTACS3 - MDTAWSH3

Ø mm	1~20
tol. D µ	0 / -30

MDTACS3 MDTAWSH3



MDCS3
MDTACS3

MDTAWSH3
DIN6527

Z3

MG

PV200

N

30°

Z3

MG

PV200

N

50°

D	d(h6)	l	L	Stock	Stock
mm 2	2	8	32	●	
3	3	12	32	●	
3	6	7	57		●
4	4	12	40	●	
4	6	8	57		●
5	5	14	50	●	
5	6	10	57		●
6	6	16	50	●	
6	6	10	57		●
7	7	20	60	●	
8	8	20	60	●	
8	8	16	63		●
9	9	20	60	●	
10	10	22	70	●	
10	10	19	72		●
12	12	22	70	●	
12	12	22	83		●
14	14	25	75	●	
14	14	22	83		●
16	16	25	75	●	
16	16	26	92		●
20	20	32	100	●	
20	20	32	104		●

● stock standard ○ non-standard stock ■ stock exhaustion

- TYPHOON
- C-SD-TA
- LFTA
- SUTA
- HSS-HSS/CO DRILLS
- UH RED
- MEX ORANGE
- HF EVO
- MEF ENDLESS
- ALU
- MDC
- G2
- MDTA**
- ULTRA MILLS
- HSS/CO
- CARBIDE BURRS
- PARAMETERS