

n **Vf**
PAGE
301~303

DIN
327

WS2 - TAWS2 - WSB2 - TAWSB2 (e8)

Ø mm	1-3	3.5-6	6.5-10	10.5-18	19-30	32-40
tol. D µ	-14 / -28	-20 / -38	-25 / -47	-32 / -59	-40 / -73	-50 / -89
tol. R µ	±20					



WS2
TAWS2

WSB2
TAWSB2

HSS/Co BR	HSS/Co PV200	HSS/Co BR	HSS/Co PV200
N	N	N BALL NOSE	N BALL NOSE

D(e8)	d(h6)	l	L	Stock	Stock	Stock	Stock
mm 1	6	2.5	47	●	●		
1.5	6	3	47	●	●		
2	6	4	48	●	●	●	○
2.5	6	5	49	●	●	●	●
3	6	5	49	●	●	●	●
3.5	6	6	50	●	●	●	●
4	6	7	51	●	●	●	●
4.5	6	7	51	●	●	●	●
5	6	8	52	●	●	●	●
5.5	6	8	52	●	●	●	●
6	6	8	52	●	●	●	●
6.5	10	10	60	●	●	●	●
7	10	10	60	●	●	○	●
7.5	10	10	60	●	●	○	●
8	10	11	61	●	●	●	●
8.5	10	11	61	●	●	●	●
9	10	11	61	●	●	●	●
9.5	10	11	61	●	●	●	●
10	10	13	63	●	●	●	●
10.5	12	13	70	●	●	●	●
11	12	13	70	●	●	●	●
11.5	12	13	70	●	●	●	●
12	12	16	73	●	●	●	●
12.5	12	16	73	●	●	●	●
13	12	16	73	●	●	●	●
13.5	12	16	73	●	●	●	●
14	12	16	73	●	●	●	●
15	12	16	73	●	●	●	●
16	16	19	79	●	●	●	●
17	16	19	79	●	●	●	●
18	16	19	79	●	●	●	●
19	16	19	79	●	●	●	●
20	20	22	88	●	●	●	●
21	20	22	88	○	●	○	●
22	20	22	88	●	●	○	●
24	25	26	102	●	○	○	●

● stock standard ○ non-standard stock ■ stock exhaustion