



PAGE  
304-305

**DIN  
844**



TAWSR ≤ Ø20  
WSFR ≤ Ø20  
TAWFSR ≤ Ø40



TAWSR ≥ Ø22  
WSFR ≥ Ø22



TAWSR - WSFR - TAWFSR (js12)

Ø mm	~6	6.5~10	10.5~18	19~30	32~40
tol. D µ	±60	±75	±90	±105	±125

					Z3-Z6	Z3-Z6	Z3-Z6	Z3
					HSS/Co PV200	HSS/Co BR	HSS/Co PV200	HSS/Co BR
					NR COARSE	HR FINE	HR FINE	ALU WR COARSE
					30°	30°	30°	45°
D(js12)	d(h6)	l	L	Z	Stock	Stock	Stock	Stock
mm 6	6	13	57	3	●	●	●	●
7	10	16	66	3	●	○	●	●
8	10	19	69	3	●	●	●	●
9	10	19	69	3	●	○	●	●
10	10	22	72	4	●	●	●	●
11	12	22	79	4	●	○	●	●
12	12	26	83	4	●	●	●	●
13	12	26	83	4	●	○	●	●
14	12	26	83	4	●	●	●	●
15	12	26	83	4	●	○	●	●
16	16	32	92	4	●	●	●	●
17	16	32	92	4	●	●	●	●
18	16	32	92	4	●	●	●	●
19	16	32	92	4	○	●	●	●
20	20	38	104	4	●	●	●	●
22	20	38	104	5			●	●
25	25	45	121	5			●	●
28	25	45	121	6			●	
30	25	45	121	6			●	
32	32	53	133	6			●	
36	32	53	133	6			●	
38	32	63	155	6			●	
40	32	63	155	6			●	

● stock standard ○ non-standard stock ■ stock exhaustion

- TYPHOON
- C-SD-TA
- LFTA
- SUTA
- HSS-HSS/CO DRILLS
- UH RED
- MEX ORANGE
- HF EVO
- MEF ENDLESS
- ALU
- MDC
- G2
- MDTA
- ULTRA MILLS
- HSS/CO
- CARBIDE BURRS
- PARAMETERS