

**n** **Vf**  
PAGE  
301~303

**DIN  
844  
1889**

WL2 - TAWL2 - WLB2 - TAWLB2 (e8)

Ø mm	1~3	3.5~6	6.5~10	10.5~18	19~30	32~40
tol. D µ	-14 / -28	-20 / -38	-25 / -47	-32 / -59	-40 / -73	-50 / -89
tol. R µ	±20					



WL2 TAWL2 	WLB2 TAWLB2 				
		HSS/Co BR	HSS/Co PV200	HSS/Co BR	HSS/Co PV200

D(e8)	d(h6)	l	L	Stock	Stock	Stock	Stock
mm 3	6	8	56	●	●	●	○
4	6	11	63	●	●	●	○
5	6	13	68	●	●	●	○
6	6	13	68	●	●	●	○
7	10	16	80	●	○	●	○
8	10	19	88	●	●	●	○
9	10	19	88	●	○	●	○
10	10	22	95	●	●	●	○
11	12	22	102	●	○	●	○
12	12	26	110	●	●	●	○
13	12	26	110	●	○	●	○
14	12	26	110	●	●	●	○
15	12	26	110	●	○	●	○
16	16	32	123	●	●	●	○
17	16	32	123	●	○	●	○
18	16	32	123	●	●	●	○
20	20	38	141	●	●	●	○
22	20	38	141	●	●	●	○
24	25	45	166	○	○	○	○
25	25	45	166	●	○	○	○
28	25	45	166	●	○	○	○
30	25	45	166	●	○	○	○
32	32	53	186	○	○	○	○
36	32	53	186	○	○	○	○
40	32	63	207	○	○	○	○

● stock standard   ○ non-standard stock   ■ stock exhaustion