

PAGE 250-251

DIN 1869
1

2691LS - 2691LSTH (h8)

Ø mm	1~3	3.1~6	6.1~10	10.1~18	18.1~20
tol. D µ	0 / -14	0 / -18	0 / -22	0 / -27	0 / -33



d = D

HSS/Co
BR

HSS/CO
PV15

D(h8)	I	L	Stock	Stock
mm 2.00	85	125	●	●
2.25	90	135	○	●
2.50	95	140	●	●
3.00	100	150	●	●
3.25	105	155	●	●
3.50	115	165	●	●
3.75	115	165	○	●
4.00	120	175	●	●
4.25	120	175	○	●
4.50	125	185	●	●
4.75	125	185	○	●
5.00	135	195	●	●
5.25	135	195	●	●
5.50	140	205	●	●
5.75	140	205	○	●
6.00	140	205	●	●
6.25	150	215	○	●
6.50	150	215	●	●
6.75	155	225	●	●
7.00	155	225	●	●
7.50	155	225	●	●
8.00	165	240	●	●
8.25	165	240	○	●
8.50	165	240	●	●
9.00	175	250	●	●
9.25	175	250	○	●
9.50	175	250	●	●
10.00	185	265	●	●
10.50	185	265	●	●
11.00	195	280	●	●
11.50	195	280	●	●
12.00	205	295	●	●
12.50	205	295	●	●
13.00	205	295	●	●

● stock standard ○ non-standard stock ■ stock exhaustion