


		DIN 345
PAGE 250-251		

145N - 145NTI - 245N (h8)

Ø mm	3.1~6	6.1~10	10.1~18	18.1~30	30.1~50	50.1~80
tol. D µ	0 / -18	0 / -22	0 / -27	0 / -33	0 / -39	0 / -46



HSS OX	HSS TiN	HSS/CO HT

D(h8)	I	L	MT	Stock	Stock	Stock
mm 5.00	52	133	1	●		
5.25	52	133	1	○		
5.50	57	138	1	●		
5.75	57	138	1	○		
6.00	57	138	1	●		
6.25	63	144	1	○		
6.50	63	144	1	●		
6.75	69	150	1	●		
7.00	69	150	1	●		
7.25	69	150	1	○		
7.50	69	150	1	●		
7.75	75	156	1	○		
8.00	75	156	1	●		
8.25	75	156	1	○		
8.50	75	156	1	●		
8.75	81	162	1	○		
9.00	81	162	1	●		
9.25	81	162	1	○		
9.50	81	162	1	●		
9.75	87	168	1	○		
10.00	87	168	1	●		
10.25	87	168	1	●		
10.50	87	168	1	●		
10.75	94	175	1	○		
11.00	94	175	1	●		
11.25	94	175	1	○		
11.50	94	175	1	●		
11.75	94	175	1	○		
12.00	101	182	1	●		
12.25	101	182	1	○		
12.50	101	182	1	●		
12.75	101	182	1	○		
13.00	101	182	1	●	●	●
13.25	108	189	1	●		
13.50	108	189	1	●	●	●
13.75	108	189	1	●		

● stock standard ○ non-standard stock ■ stock exhaustion