

n **Vf**
PAGE 250-251

DIN 345

145N - 145NTI - 245N (h8)

Ø mm	3.1~6	6.1~10	10.1~18	18.1~30	30.1~50	50.1~80
tol. D µ	0 / -18	0 / -22	0 / -27	0 / -33	0 / -39	0 / -46



HSS OX	HSS TiN	HSS/CO HT

D(h8)	I	L	MT	Stock	Stock	Stock
mm 32.00	185	334	4	●		
32.50	185	334	4	●		
33.00	185	334	4	●		
33.50	185	334	4	●		
34.00	190	339	4	●		
34.50	190	339	4	●		
35.00	190	339	4	●		
35.50	190	339	4	●		
36.00	195	344	4	●		
36.50	195	344	4	●		
37.00	195	344	4	●		
37.50	195	344	4	●		
38.00	200	349	4	●		
38.50	200	349	4	●		
39.00	200	349	4	●		
39.50	200	349	4	●		
40.00	200	349	4	●		
40.50	205	354	4	○		
41.00	205	354	4	●		
41.50	205	354	4	○		
42.00	205	354	4	●		
42.50	205	354	4	○		
43.00	210	359	4	●		
43.50	210	359	4	○		
44.00	210	359	4	●		
44.50	210	359	4	○		
45.00	210	359	4	●		
45.50	215	364	4	○		
46.00	215	364	4	●		
46.50	215	364	4	○		
47.00	215	364	4	●		
47.50	215	364	4	○		
48.00	220	369	4	●		
48.50	220	369	4	○		
49.00	220	369	4	●		
49.50	220	369	4	○		

● stock standard ○ non-standard stock ■ stock exhaustion

- TYPHOON
- C-SD-TA
- LFTA
- SUTA
- HSS-HSS/CO DRILLS
- UH RED
- MEX ORANGE
- HF EVO
- MEF ENDLESS
- ALU
- MDC
- G2
- MDTA
- ULTRA MILLS
- HSS/CO
- CARBIDE BURRS
- PARAMETERS