

PAGE 250-251

DIN 1870
1-2

2701LS - 2702LS (h8)

Ø mm	1~3	3.1~6	6.1~10	10.1~18	18.1~30
tol. D µ	0 / -14	0 / -18	0 / -22	0 / -27	0 / -33



HSS/Co
BR

HSS/Co
BR

D(h8)	I	L	MT	Stock	Stock
mm 13.00	205	310	1	●	●
13.00	260	395	1	●	●
13.50	220	325	1	●	●
13.50	275	410	1	●	●
14.00	220	325	1	●	●
14.00	275	410	1	●	●
14.50	220	340	2	●	●
14.50	275	425	2	●	●
15.00	220	340	2	●	●
15.00	275	425	2	●	●
15.50	230	355	2	●	●
15.50	295	445	2	●	●
16.00	230	355	2	●	●
16.00	295	445	2	●	●
16.50	230	355	2	●	●
16.50	295	445	2	●	●
17.00	230	355	2	●	●
17.00	295	445	2	●	●
17.50	245	370	2	●	●
17.50	310	465	2	●	●
18.00	245	370	2	●	●
18.00	310	465	2	●	●
18.50	245	370	2	●	●
18.50	310	465	2	●	●
19.00	245	370	2	●	●
19.00	310	465	2	●	●
19.50	260	385	2	●	●
19.50	325	490	2	●	●
20.00	260	385	2	●	●
20.00	325	490	2	●	●
21.00	260	385	2	●	●
21.00	325	490	2	●	●
22.00	270	405	2	●	●
22.00	345	515	2	●	●
23.00	270	405	2	●	●
23.00	345	515	2	●	●

● stock standard ○ non-standard stock ■ stock exhaustion